



MERCATOR
NAVIGATING SUCCESS

Project Name: _____

Location: _____

Item #: _____ Qty: _____

Model: _____

M1R23G / M2R49G / M3R72G Glass Door Reach-In Refrigerators

MODEL: ☐ M1R23G ☐ M2R49G ☐ M3R72G

SPECIAL FEATURES

Exterior:

- 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- Security lock with key
- Rollers (4) and leveling feet (2)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (4)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor



M1R23G




M2R49G




M3R72G

TECHNICAL DATA


MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMP. RANGE	ELECTRICAL	AMP DRAW	REFRIGERANT	DOORS / SHELVES	NET WEIGHT
M1R23G	27" x 35" x 81" (690 x 891 x 2056 mm)	22 1/4" x 29" x 51 3/8" (566 x 735 x 1305 mm)	19 Cu Ft (542 L)	34°F to 40°F (2°C to 5°C)	115V / 60Hz / 1PH	1.9A	R600a	1 / 3	212 lbs (96 kg)
M2R49G	54" x 35" x 81" (1376 x 891 x 2056 mm)	49" x 27" x 60" (1252 x 735 x 1305 mm)	42 Cu Ft (1191 L)	34°F to 40°F (2°C to 5°C)	115V / 60Hz / 1PH	3.3A	R290	2 / 6	355 lbs (161 kg)
M3R72G	81 1/5" x 35" x 81" (2062 x 891 x 2056 mm)	76 3/10" x 29" x 51 3/8" (1938 x 735 x 1305 mm)	65 Cu Ft (1841 L)	34°F to 41°F (2°C to 5°C)	115V / 60Hz / 1PH	6.6A	R290	3 / 9	514 lbs (233 kg)



FRONT



FRONT



FRONT



NEMA 5-15P



Intertek



Intertek

Available in export voltages and plug types.

WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.

© 2026 MERCATOR