



MERCATOR
NAVIGATING SUCCESS

Project Name: _____

Location: _____

Item #: _____ Qty: _____

Model: _____

M1R23 / M2R49 / M3R72 Solid Door Reach-In Value Refrigerators

MODEL: ☐ M1R23 ☐ M2R49 ☐ M3R72

SPECIAL FEATURES

Exterior:

- 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- Security lock with key
- Rollers (4) and leveling feet (2)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (4)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor



M1R23




M2R49




M3R72

TECHNICAL DATA


MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMP. RANGE	ELECTRICAL	AMP DRAW	REFRIGERANT	DOORS / SHELVES	NET WEIGHT
M1R23	27" x 34" x 81" (690 x 864 x 2056 mm)	22 1/4" x 29" x 51 3/8" (566 x 735 x 1305 mm)	23 Cu Ft (542 L)	34°F to 40°F (2°C to 5°C)	115V / 60Hz / 1PH	2.2A	R-600a	1 / 3	195 lbs (88.5 kg)
M2R49	54" x 34" x 81" (1376 x 864 x 2056 mm)	49 1/4" x 29" x 51 3/8" (1252 x 735 x 1305 mm)	42 Cu Ft (1191 L)	34°F to 40°F (2°C to 5°C)	115V / 60Hz / 1PH	3.1A	R290	2 / 6	317 lbs (144 kg)
M3R72	81" x 34" x 81" (2062 x 864 x 2056 mm)	76 1/4" x 29" x 51 3/8" (1938 x 735 x 1305 mm)	65 Cu Ft (1841 L)	34°F to 40°F (2°C to 5°C)	115V / 60Hz / 1PH	3.4A	R290	3 / 9	444 lbs (201.5 kg)



FRONT



FRONT



FRONT



NEMA 5-15P



Intertek



Intertek

Available in export voltages and plug types.

WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.

© 2026 MERCATOR