

MERCATOR



KITCHEN EQUIPMENT

Refrigeration, Mixers, Food Warmers and Meat Slicers, Beverage Dispensers, Granita Machines

Table of Contents

4



The Smart
Way to Scale
Your Kitchen

5



Reach-In
Refrigerators

12



Reach-In
Freezers

15



Merchandisers

17



Undercounter
Refrigeration

21



Undercounter
Freezers

23



Worktop
Refrigeration

25



Worktop
Freezers

27



Prep Tables

33



Planetary
Mixers

35



Food Warmer

36



Meat Slicers

37



Beverage
Dispensers

38



Granita Machine

MERCATOR

At **Mercator**, we know your kitchen doesn't have time for downtime. That's why we deliver **durable, US-certified commercial equipment** designed to perform under pressure—whether you're cooking, chilling, cleaning, or serving. Backed by **fast delivery, competitive pricing**, and **reliable warranty programs**, Mercator gives you a one-stop solution to keep operations running smoothly and budgets on track.

Performance You Can Count On

Durable US-certified kitchen equipment engineered for high-volume performance.

Smart Budgets

Highly competitive prices that lower your total cost of ownership.



Strategically stocked inventory to minimize downtime.

Certified & Safe

ETL listed for compliance and peace of mind.

Backed with Confidence

Every product comes with responsive customer support.

One-Stop Solution

From hot kitchens to cold storage to cleanup, Mercator covers your operation end to end.



Reach-In Refrigerators

Durable refrigerated storage with precise temperature control to keep kitchens running smoothly.

Specification	MR1	MR2
External Dimensions (W x D x H)	29" x 32 1/4" x 82 1/2" (737 x 819 x 2096 mm)	54" x 32 1/4" x 82 1/2" (1372 x 819 x 2096 mm)
Internal Dimensions (W x D x H)	24" x 27" x 60" (610 x 686 x 1524 mm)	49" x 27" x 60" (1245 x 686 x 1524 mm)
Interior Volume	23 Cu Ft (651 L)	46 Cu Ft (1303 L)
Holding Temp. Range	33°F to 40°F (1°C to 4°C)	33°F to 40°F (1°C to 4°C)
Electrical	115V / 60Hz / 1PH	115V / 60Hz / 1PH
Connection Rating Amp	3.6A	6.2A
Refrigerant	R-290	R-290
Doors / Shelves	1 / 3	2 / 6
Net Weight	282 lbs (128 kg)	448 lbs (203 kg)

Reach-In Refrigerators



MR1

1 Door Reach-In Refrigerator
23 Cu. Ft.

Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- Security lock with key
- Casters (4)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (3)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor



MR2

2 Door Reach-In Refrigerator
46 Cu. Ft.

Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- Security lock with key
- Casters (4)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (6)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor

Value Reach-In Refrigerators

Cost-effective reach-in refrigerators built for dependable, everyday performance.

Specification	M1R23	M2R49	M3R72
External Dimensions (W x D x H)	27" x 34" x 81" (690 x 864 x 2056 mm)	54" x 34" x 81" (1376 x 864 x 2056 mm)	81" x 34" x 81" (2062 x 864 x 2056 mm)
Internal Dimensions (W x D x H)	22 1/4" x 29" x 51 3/8" (566 x 735 x 1305 mm)	49 1/4" x 29" x 51 3/8" (1252 x 735 x 1305 mm)	76 1/4" x 29" x 51 3/8" (1938 x 735 x 1305 mm)
Interior Volume	23 Cu Ft (542 L)	42 Cu Ft (1191 L)	65 Cu Ft (1841 L)
Holding Temp. Range	34°F to 40°F (2°C to 5°C)	34°F to 40°F (2°C to 5°C)	34°F to 40°F (2°C to 5°C)
Electrical	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1PH
Connection Rating Amp	2.2A	3.1A	3.4A
Refrigerant	R-600a	R-290	R-290
Doors / Shelves	1 / 3	2 / 6	2 / 6
Net Weight	195 lbs (88.5 kg)	317 lbs (144 kg)	444 lbs (201.5 kg)

Value Reach-In Refrigerators



M1R23

1 Door Reach-In Refrigerator
23 Cu. Ft.

Exterior:

- 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- Security lock with key
- Rollers (4) and leveling feet (2)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (3)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor



M2R49

2 Door Reach-In Refrigerator
42 Cu. Ft.

Exterior:

- 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- Security lock with key
- Rollers (4) and leveling feet (2)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (6)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor



M3R72

3 Door Reach-In Refrigerator
65 Cu. Ft.

Exterior:

- 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- Security lock with key
- Rollers (4) and leveling feet (2)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (9)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor





Glass Door Reach-In Refrigerators

Glass door reach-in refrigerators for quick product visibility and consistent temperature control.

Specification	M1R23G	M2R49G	M3R72G
External Dimensions (W x D x H)	27" x 35" x 81" (690 x 891 x 2056 mm)	54" x 35" x 81" (1376 x 891 x 2056 mm)	81" x 32" x 83" (2057 x 813 x 2108 mm)
Internal Dimensions (W x D x H)	22 1/4" x 29" x 51 3/8" (566 x 735 x 1305 mm)	49" x 27" x 60" (1252 x 735 x 1305 mm)	-
Interior Volume	19 Cu Ft (542 L)	42 Cu Ft (1191 L)	-
Holding Temp. Range	34°F to 40°F (2°C to 5°C)	34°F to 40°F (2°C to 5°C)	34°F to 40°F (2°C to 5°C)
Electrical	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1PH
Connection Rating Amp	1.9A	3.3A	-
Refrigerant	R600a	R-290	R-290
Doors / Shelves	1 / 3	2 / 6	3 / 9
Net Weight	212 lbs (96 kg)	355 lbs (161 kg)	704 lbs (319 kg)

Glass Door Reach-In Refrigerators



M1R23G

1 Door Glass Reach-In Refrigerator
27 Cu. Ft.

Exterior:

- 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- Security lock with key
- Rollers (4) and leveling feet (2)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (3)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor



M2R49G

2 Door Glass Reach-In Refrigerator
54 Cu. Ft.

Exterior:

- Exterior:
- 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- Security lock with key
- Rollers (4) and leveling feet (2)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (6)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor



M3R72G

3 Door Glass Reach-In Refrigerator
54 Cu. Ft.

Exterior:

- Exterior:
- 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- Security lock with key
- Rollers (4) and leveling feet (2)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (9)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor





Reach-In Freezers

Lock in freshness with consistent sub-zero performance built for high-volume kitchens.

Specification	MF1	MF2
External Dimensions (W x D x H)	29" x 32 1/4" x 82 1/2" (737 x 819 x 2096 mm)	54" x 32 1/4" x 82 1/2" (1372 x 819 x 2096 mm)
Internal Dimensions (W x D x H)	24 3/8" x 27" x 60" (619 x 686 x 1524 mm)	49" x 27" x 60" (1245 x 686 x 1524 mm)
Interior Volume	23 Cu Ft (651 L)	46 Cu Ft (1303 L)
Holding Temp. Range	-7°F to 0°F (-22°C to -18°C)	-7°F to 0°F (-22°C to -18°C)
Compressor Power	0.67 HP	1.29 HP
Electrical	115V / 60Hz / 1 PH	115V / 60Hz / 1 PH
Connection Rating Amp	4.2A	8.5A
Refrigerant	R-290	R-290
Doors / Shelves	1 / 3	2 / 6
Net Weight	283 lbs (128 kg)	478 lbs (217 kg)

Reach-In Freezers

MF1

1 Door Reach-In Freezer
23 Cu. Ft.



Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- Security lock with key
- Casters (4)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (3)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor

MF2

2 Door Reach-In Freezer
46 Cu. Ft.



Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- Security lock with key
- Casters (4)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (6)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor



NEMA 5-15p



Intertek



Intertek

mercatorfs.com

Value Reach-In Freezers

Budget-friendly reach-in freezers designed for reliable, consistent freezing.

Specification	M1F23	M2F49	M3F72
External Dimensions (W x D x H)	27" x 34" x 81" (690 x 864 x 2056 mm)	54" x 34" x 81" (1376 x 864 x 2056 mm)	81" x 34" x 81" (2062 x 864 x 2056 mm)
Internal Dimensions (W x D x H)	22 1/4" x 29" x 51 3/8" (566 x 735 x 1305 mm)	49 1/4" x 29" x 51 3/8" (1252 x 735 x 1305 mm)	76 1/4" x 29" x 51 3/8" (1938 x 735 x 1305 mm)
Interior Volume	23 Cu Ft (542 L)	42 Cu Ft (1191 L)	65 Cu Ft (1841 L)
Holding Temp. Range	-10°F to 10°F (-23°C to 12C)	-10°F to 10°F (-23°C to 12C)	-10°F to 10°F (-23°C to 12C)
Electrical	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1PH
Connection Rating Amp	2.2A	3.1A	3.4A
Refrigerant	R-600a	R-290	R-290
Doors / Shelves	1 / 3	2 / 6	2 / 6
Net Weight	195 lbs (88.5 kg)	317 lbs (144 kg)	444 lbs (201.5 kg)

Value Reach-In Freezers



M1F23

1 Door Value Reach-In Freezer
23 Cu. Ft.

Exterior:

- 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- Security lock with key
- Rollers (4) and leveling feet (2)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (3)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor



M2F49

2 Door Value Reach-In Freezer
42 Cu. Ft.

Exterior:

- 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- Security lock with key
- Rollers (4) and leveling feet (2)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (6)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor



M3F72

3 Door Value Reach-In Freezer
65 Cu. Ft.

Exterior:

- 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- Security lock with key
- Rollers (4) and leveling feet (2)

Interior:

- 201 stainless steel
- Fully adjustable heavy-duty epoxy-coated wire shelves (9)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor





Merchandiser Refrigerators

Showcase and sell more with brilliant LED lighting, reliable cooling, and built-in branding space.

Specification	MRM1	MRM2	MRM25
External Dimensions (W x D x H)	27" x 32" x 79 1/2" (686 x 810 x 2019 mm)	54" x 32" x 79 1/2" (1372 x 810 x 2019 mm)	54" x 32" x 79 1/2" (1372 x 810 x 2019 mm)
Internal Dimensions (W x D x H)	26 1/2" x 22" x 52 1/4" (673 x 559 x 1327 mm)	49 1/4" x 26 1/2" x 52 1/4" (1251 x 673 x 1327 mm)	49 1/4" x 26 1/2" x 52 1/4" (1251 x 673 x 1327 mm)
Interior Volume	23 Cu Ft (651 L)	48 Cu Ft (1359 L)	48 Cu Ft (1359 L)
Holding Temp. Range	33°F to 41°F (1°C to 5°C)	33°F to 41°F (1°C to 5°C)	33°F to 41°F (1°C to 5°C)
Electrical	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1PH
Connection Rating Amp	3.0A	4.5A	4.5A
Refrigerant	R-290 (3.0 oz)	R-290 (3.7 oz)	R-290 (3.7 oz)
Doors / Shelves	1 / 4	2 / 8	2 sliding / 8
Net Weight	325 lbs (148 kg)	490 lbs (223 kg)	490 lbs (223 kg)

Merchandiser Refrigerators

MRM1

1 Door Merchandiser Refrigerator
23 Cu. Ft. / Swing Door



Exterior:

- Constructed of powder coated steel
- Top backlit display panel for customized advertising
- Insulated triple-paned, self-closing glass door
- Digital controls and LED temperature display
- Security lock with key
- Casters (4) and leveling feet (2)
- No drain required

Interior:

- Walls: powder coated aluminum
- Fully adjustable heavy-duty wire shelves (4)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor

MRM2

2 Door Merchandiser Refrigerator
48 Cu. Ft. / Swing Door



Exterior:

- Constructed of powder coated steel
- Top backlit display panel for customized advertising
- Insulated triple-paned, self-closing glass door
- Digital controls and LED temperature display
- Security lock with key
- Casters (4) and leveling feet (2)
- No drain required

Interior:

- Walls: powder coated aluminum
- Fully adjustable heavy-duty wire shelves (4)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor

MRM25

2 Door Merchandiser Refrigerator
48 Cu. Ft. / Sliding Door



Exterior:

- Constructed of powder coated steel
- Top backlit display panel for customized advertising
- Insulated triple-paned, self-closing glass door
- Digital controls and LED temperature display
- Security lock with key
- Casters (4) and leveling feet (2)
- No drain required

Interior:

- Walls: powder coated aluminum
- Fully adjustable heavy-duty wire shelves (4)
- LED lighting
- Auto-defrost system
- Bottom-mount compressor



Undercounter Refrigeration

Compact cold storage that maximizes workspace and keeps ingredients within reach.

Specification	MUR27	MUR48	MUR60
External Dimensions (W x D x H)	27" x 29 1/2" x 35 1/4" (686 x 749 x 894 mm)	47 1/4" x 29 1/2" x 35 1/4" (1199 x 749 x 894 mm)	60 1/4" x 29 1/2" x 35 1/4" (1529 x 749 x 895 mm)
Internal Dimensions (W x D x H)	22 3/8" x 19 3/4" x 23 1/2" (568 x 502 x 597 mm)	42 5/8" x 19 3/4" x 23 1/2" (1084 x 502 x 597 mm)	55" x 19 3/4" x 23 1/2" (1397 x 502 x 597 mm)
Interior Volume	6 Cu Ft (170 L)	12 Cu Ft (340 L)	17 Cu Ft (481 L)
Holding Temp. Range	32°F to 40°F (0°C to 4°C)	32°F to 40°F (0°C to 4°C)	32°F to 40°F (0°C to 4°C)
Compressor Power	0.17 HP	0.20 HP	0.20 HP
Electrical	115V / 60Hz / 1 PH	115V / 60Hz / 1 PH	115V / 60Hz / 1 PH
Connection Rating Amp / Watts	1.8A / 210W	2.4A / 270W	2.6A / 285W
Refrigerant	R-290	R-290	R-290
Net Weight	154 lbs (70 kg)	209 lbs (95 kg)	282 lbs (128 kg)
Gross Weight	207 lbs (94 kg)	300 lbs (136 kg)	326 lbs (148 kg)

Undercounter Refrigeration



MUR27

1 Door Undercounter Refrigerator
6.3 Cu. Ft.

Exterior:

- Constructed of 403 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- Painted aluminum
- Adjustable plastic coated steel shelves (1 per section; 90 lbs load capacity ea.)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



MUR48

2 Door 48" Undercounter Refrigerator
12 Cu. Ft.

Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- Painted aluminum
- Adjustable plastic coated steel shelves (1 per section; 90 lbs load capacity ea.)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



MUR60

2 Door 60" Undercounter Refrigerator
15 Cu. Ft.

Exterior:

- Constructed of 403 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gaskets
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- Painted aluminum
- Adjustable plastic coated steel shelves (1 per section; 90 lbs load capacity ea.)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



NEMA 5-15p



Intertek



Intertek

Value Undercounter Refrigeration

Compact cold storage that maximizes workspace and keeps ingredients within reach.

Specification	MR27U	MR48U	MR60U	MR72U
External Dimensions (W x D x H)	27 3/4" x 30 1/2" x 37 1/2" (705 x 775 x 953 mm)	48 1/2" x 30 1/2" x 37 1/2" (1230 x 775 x 953 mm)	60 1/4" x 30 1/2" x 37 1/2" (1530 x 775 x 953 mm)	71 3/4" x 30 1/2" x 37 1/2" (1822 x 775 x 953 mm)
Internal Dimensions (W x D x H)	24 3/4" x 21" x 27" (630 x 533 x 685 mm)	44 1/4" x 21" x 27" (1125 x 533 x 685 mm)	56" x 21" x 27" (1425 x 533 x 685 mm)	67 1/2" x 19 3/4" x 23 1/2" (1717 x 533 x 685 mm)
Interior Volume	7.3 Cu Ft (205 L)	12.9 Cu Ft (364 L)	16.3 Cu Ft (462 L)	19.6 Cu Ft (554 L)
Doors/Shelves	1/1	2/2	2/2	2/2
Electrical	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1 PH
Refrigerant	R-600a	R-600a	R-290	R-290

Value Undercounter Refrigeration



MR27U

1 Door 27" Undercounter Refrigerator
7.3 Cu. Ft.

Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated steel shelves
- (1 per section; 90 lbs load capacity each)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



MR48U

2 Door 48" Undercounter Refrigerator
12.9 Cu. Ft.

Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated steel shelves
- (1 per section; 90 lbs load capacity each)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



MR60U

2 Door 60" Undercounter Refrigerator
16.3 Cu. Ft.

Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated steel shelves
- (1 per section; 90 lbs load capacity each)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



MR72U

3 Door 71" Undercounter Refrigerator
19.6 Cu. Ft.

Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated steel shelves
- (1 per section; 90 lbs load capacity each)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



NEMA 5-15p



Intertek



Intertek

mercatorfs.com

Value Undercounter Freezer

Compact cold storage that maximizes workspace and keeps ingredients within reach.

Specification	MF27U	MF48U	MF60U	MF72U
External Dimensions (W x D x H)	27 3/4" x 30 1/2" x 37 1/2" (705 x 775 x 953 mm)	48 1/2" x 30 1/2" x 37 1/2" (1230 x 775 x 953 mm)	60 1/4" x 30 1/2" x 37 1/2" (1530 x 775 x 953 mm)	71 3/4" x 30 1/2" x 37 1/2" (1822 x 775 x 953 mm)
Internal Dimensions (W x D x H)	24 3/4" x 21" x 27" (630 x 533 x 685 mm)	44 1/4" x 21" x 27" (1125 x 533 x 685 mm)	56" x 21" x 27" (1425 x 533 x 685 mm)	67 1/2" x 19 3/4" x 23 1/2" (1717 x 533 x 685 mm)
Interior Volume	7.3 Cu Ft (205 L)	12.9 Cu Ft (364 L)	16.3 Cu Ft (462 L)	19.6 Cu Ft (554 L)
Doors/Shelves	1/1	2/2	2/2	2/2
Electrical	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1 PH
Refrigerant	R-600a	R-600a	R-290	R-290

Value Undercounter Freezer

MF27U

1 Door 27" Undercounter Freezer
7.3 Cu. Ft.



Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated steel shelves
- (1 per section; 90 lbs load capacity each)
- Auto-defrost system
- Holding temperature: -10°F to 10°F (-23°C to -12°C)

MF48U

2 Door 48" Undercounter Freezer
12.9 Cu. Ft.



Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated steel shelves
- (1 per section; 90 lbs load capacity each)
- Auto-defrost system
- Holding temperature: -10°F to 10°F (-23°C to -12°C)

MF60U

2 Door 60" Undercounter Freezer
16.3 Cu. Ft.



Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated steel shelves
- (1 per section; 90 lbs load capacity each)
- Auto-defrost system
- Holding temperature: -10°F to 10°F (-23°C to -12°C)

MF72U

2 Door 71" Undercounter Freezer
19.6 Cu. Ft.



Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated steel shelves
- (1 per section; 90 lbs load capacity each)
- Auto-defrost system
- Holding temperature: -10°F to 10°F (-23°C to -12°C)





Worktop Refrigeration

Compact cold storage that maximizes workspace and keeps ingredients within reach.

Specification	MR27UWT	MR48UWT	MR60UWT	MR72UWT
External Dimensions (W x D x H)	27 3/4" x 30 1/2" x 41 1/2" (705 x 775 x 1053 mm)	48 1/2" x 30 1/2" x 41 1/2" (1230 x 775 x 1053 mm)	60 1/4" x 30 1/2" x 41 1/2" (1530 x 775 x 1053 mm)	71 3/4" x 30 1/2" x 41 1/2" (1822 x 775 x 1053 mm)
Internal Dimensions (W x D x H)	24 3/4" x 21" x 27" (630 x 533 x 685 mm)	44 1/4" x 21" x 27" (1125 x 533 x 685 mm)	56" x 21" x 27" (1425 x 533 x 685 mm)	67 1/2" x 19 3/4" x 23 1/2" (1717 x 533 x 685 mm)
Interior Volume	7.3 Cu Ft (205 L)	12.9 Cu Ft (364 L)	16.3 Cu Ft (462 L)	19.6 Cu Ft (554 L)
Doors/Shelves	1/1	2/2	2/2	2/2
Electrical	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1 PH
Refrigerant	R-600a	R-600a	R-290	R-290

Worktop Refrigerator

MR27UWT

1 Door 27" Undercounter Refrigerator
7.3 Cu. Ft.



Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated steel shelves
- (1 per section; 90 lbs load capacity each)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)

MR48UWT

2 Door 48" Undercounter Refrigerator
12.9 Cu. Ft.



Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated steel shelves
- (1 per section; 90 lbs load capacity each)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)

MR60UWT

2 Door 60" Undercounter Refrigerator
16.3 Cu. Ft.



Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated steel shelves
- (1 per section; 90 lbs load capacity each)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)

MR72UWT

3 Door 71" Undercounter Refrigerator
19.6 Cu. Ft.



Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated steel shelves
- (1 per section; 90 lbs load capacity each)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



NEMA 5-15p



Intertek



Intertek

mercatorfs.com

Worktop Freezers

Compact cold storage that maximizes workspace and keeps ingredients within reach.

Specification	MF27UWT	MF48UWT	MF60UWT	MF72UWT
External Dimensions (W x D x H)	27 3/4" x 30 1/2" x 41 1/2" (705 x 775 x 1053 mm)	48 1/2" x 30 1/2" x 41 1/2" (1230 x 775 x 1053 mm)	60 1/4" x 30 1/2" x 41 1/2" (1530 x 775 x 1053 mm)	71 3/4" x 30 1/2" x 41 1/2" (1822 x 775 x 1053 mm)
Internal Dimensions (W x D x H)	24 3/4" x 21" x 27" (630 x 533 x 685 mm)	44 1/4" x 21" x 27" (1125 x 533 x 685 mm)	56" x 21" x 27" (1425 x 533 x 685 mm)	67 1/2" x 19 3/4" x 23 1/2" (1717 x 533 x 685 mm)
Interior Volume	7.3 Cu Ft (205 L)	12.9 Cu Ft (364 L)	16.3 Cu Ft (462 L)	19.6 Cu Ft (554 L)
Doors/Shelves	1/1	2/2	2/2	2/2
Electrical	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1 PH
Refrigerant	R-600a	R-290	R-290	R-290

Worktop Freezer



MF27UWT

1 Door 27" Undercounter Freezer
7.3 Cu. Ft.

Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated steel shelves
- (1 per section; 90 lbs load capacity each)
- Auto-defrost system
- Holding temperature:
• -10°F to 10°F (-23°C to -12°C)



MF48UWT

2 Door 48" Undercounter Freezer
12.9 Cu. Ft.

Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated steel shelves
- (1 per section; 90 lbs load capacity each)
- Auto-defrost system
- Holding temperature:
• -10°F to 10°F (-23°C to -12°C)



MF60UWT

2 Door 60" Undercounter Freezer
16.3 Cu. Ft.

Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated steel shelves
- (1 per section; 90 lbs load capacity each)
- Auto-defrost system
- Holding temperature:
• -10°F to 10°F (-23°C to -12°C)



MF72UWT

3 Door 72" Undercounter Freezer
19.6 Cu. Ft.

Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated steel shelves
- (1 per section; 90 lbs load capacity each)
- Auto-defrost system
- Holding temperature:
• -10°F to 10°F (-23°C to -12°C)



NEMA 5-15p



Intertek



Intertek

mercatorfs.com



Streamline prep with chilled topping compartments, full-length cutting boards, and dependable cold holding.

Specification	MPT27	MPT48	MPT60
External Dimensions (WxDxH)	27 1/2" x 29 1/2" x 41 1/2" (699 x 749 x 1054 mm)	46 3/4" x 29 1/2" x 41 1/2" (1187 x 749 x 1054 mm)	60 1/4" x 29 1/2" x 41 1/2" (1530 x 749 x 1054 mm)
Internal Dimensions (W x D x H)	24 1/4" x 19 3/4" x 23 1/2" (616 x 502 x 597 mm)	43" x 19 3/4" x 23 1/2" (1092 x 502 x 597 mm)	56 1/4" x 19 3/4" x 23 1/2" (1429 x 502 x 597 mm)
Interior Volume	6 Cu Ft (170 L)	12 Cu Ft (340 L)	15 Cu Ft (425 L)
Holding Temp. Range	33°F to 40°F (1°C to 4°C)	33°F to 40°F (1°C to 4°C)	33°F to 40°F (1°C to 4°C)
Electrical	0.43 HP	0.56 HP	0.33 HP
Connection Rating Amp / Watts	3.6A / 360W	4.9A / 490W	5.4A / 540W
Refrigerant	R-290	R-290	R-290
Net Weight	176 lbs (80 kg)	253 lbs (115 kg)	306 lbs (139 kg)
Gross Weight	220 lbs (100 kg)	220 lbs (100 kg)	363 lbs (165 kg)

Prep Tables



MPT27

1 Door 27" Refrigerated Prep Table

Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Equipped with 3/4" thick removable polyethylene cutting board
- Topping section holds a variety of food pans up to 6" deep
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



MPT48

2 Door 48" Refrigerated Prep Table

Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Equipped with 3/4" thick removable polyethylene cutting board
- Topping section holds a variety of food pans up to 6" deep
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



MPT60

2 Door 60" Refrigerated Prep Table

Exterior:

- Constructed of 430 stainless steel
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket
- Recessed handles for easy opening/closing
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Equipped with 3/4" thick removable polyethylene cutting board
- Topping section holds a variety of food pans up to 6" deep
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



NEMA 5-15p



Intertek



Intertek

mercatorfs.com

Value Prep Tables

Efficient prep tables combining refrigerated storage with organized ingredient access for fast-paced kitchens.

Specification	MRPT27	MRPT48	MRPT60	MRPT72
External Dimensions (WxDxH)	27 3/4" x 30 1/2" x 44 1/2" (705 x 775 x 1130 mm)	48 1/2" x 30 1/2" x 44 1/4" (1230 x 775 x 1124 mm)	60 1/4" x 30 1/4" x 44 1/4" (1530 x 770 x 1124 mm)	71 3/4" x 30 1/4" x 44 1/4" (1822 x 770 x 1124 mm)
Internal Dimensions (W x D x H)	24 3/4" x 21" x 27" (630 x 533 x 685 mm)	44 1/4" x 21" x 27" (1125 x 533 x 685 mm)	56" x 21" x 27" (1425 x 533 x 685 mm)	67 1/2" x 19 3/4" x 23 1/2" (1717 x 533 x 685 mm)
Interior Volume	7.3 Cu Ft (205 L)	12.9 Cu Ft (364 L)	16.3 Cu Ft (462 L)	19.6 Cu Ft (554 L)
Doors/ Shelves	1 / 1	2 / 2	2 / 2	2 / 2
½ Pans	8	12	16	18
Electrical	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1PH
Refrigerant	R-600a	R-290	R-290	R-290

Value Prep Tables



MRPT27

1 Door 27" Refrigerated Prep Table

Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



MRPT48

2 Door 48" Refrigerated Prep Table

Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



MRPT60

2 Door 60" Refrigerated Prep Table

Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



MRPT72

3 Door 72" Refrigerated Prep Table

Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



NEMA 5-15p



Intertek



Intertek

mercatorfs.com



Mega Top Prep Tables

Efficient prep tables combining refrigerated storage with organized ingredient access for fast-paced kitchens.

Specification	MRPT27M	MRPT48M	MRPT60M	MRPT72M
External Dimensions (WxDxH)	27 3/4" x 30 1/2" x 44 1/2" (705 x 775 x 1130 mm)	48 1/2" x 30 1/2" x 44 1/4" (1230 x 775 x 1124 mm)	60 1/4" x 30 1/4" x 44 1/4" (1530 x 770 x 1124 mm)	71 3/4" x 30 1/4" x 44 1/4" (1822 x 770 x 1124 mm)
Internal Dimensions (W x D x H)	24 3/4" x 21" x 27" (630 x 533 x 685 mm)	44 1/4" x 21" x 27" (1125 x 533 x 685 mm)	56" x 21" x 27" (1425 x 533 x 685 mm)	67 1/2" x 19 3/4" x 23 1/2" (1717 x 533 x 685 mm)
Interior Volume	7.3 Cu Ft (205 L)	12.9 Cu Ft (364 L)	16.3 Cu Ft (462 L)	19.6 Cu Ft (554 L)
Doors/ Shelves	1 / 1	2 / 2	2 / 2	2 / 2
½ Pans	12	18	24	30
Electrical	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1PH	115V / 60Hz / 1PH
½ Pans	12	18	24	30
Refrigerant	R-600a	R-290	R-290	R-290

Mega Top Prep Tables



MRPT27M

1 Door 27" Refrigerated Prep Table

Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



MRPT48M

2 Door 48" Refrigerated Prep Table

Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



MRPT60M

2 Door 60" Refrigerated Prep Table

Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



MRPT72M

3 Door 72" Refrigerated Prep Table

Exterior:

- 430 stainless steel door, sides, and top
- Self-closing doors; >90° stay-open feature
- Magnetic door gasket(s)
- Recessed handles for easy opening/cleaning
- Digital controls and LED temperature display
- (4) 4" casters - 2 locking, 2 non-locking

Interior:

- 201 stainless steel
- Adjustable plastic coated wire shelves (1 per section; 90 lbs load capacity ea.)
- Auto-defrost system
- Holding temperature: 33°F to 41°F (1°C to 5°C)



NEMA 5-15p



Intertek



Intertek

Planetary Mixers

Versatile, gear-driven power for mixing, beating, or whipping—day after day.

Specification	MPM10	MPM20	MPM30
External Dimensions (W x D x H)	15 5/8" x 15 5/8" x 15 5/8"	21 15/16" x 22" x 31 5/16"	22 13/16" x 24 1/8" x 45"
Capacity	10Qt (10L)	20Qt (20L)	30Qt (30L)
Electrical	120 Volts / 60 Hz / 1 PH	120 Volts / 60 Hz / 1 PH	120 Volts / 60 Hz / 1 PH
Connection Rating Amp / Watts	10A / 750 Watts	14A / 1100 Watts	20A / 1500 Watts
Lift Type	Manual	Manual	Manual
RPM	108, 195, 355	108, 195, 355	91, 166, 282
Speed	3 Speed	3 Speed	3 Speed
Transmission Type	Gear-Driven	Gear-Driven	Gear-Driven
Net Weight	79.4 lbs (36 kg)	141.1 lbs (64 kg)	286.6 lbs (130 kg)

Planetary Mixers



MPM10

10 Qt. Planetary Stand Mixer

Special Features:

- Powerful 3-speed motor; gear-driven transmission to withstand daily use
- Durable 10 qt stainless steel bowl; wire bowl guard for added safety
- Includes wire whip, flat beater, and dough hook
- Easy to use with simple on/off buttons and manually operated bowl lift
- 120V, 750W, 1 hp, up to 355 RPM



MPM20

20 Qt. Planetary Stand Mixer

Special Features:

- Powerful 3-speed motor; gear-driven transmission to withstand daily use
- Durable 20 qt stainless steel bowl; wire bowl guard for added safety
- Includes wire whip, flat beater, and dough hook
- Easy to use with simple on/off buttons and manually operated bowl lift
- 120V, 1100W, 1 1/2 hp, up to 355 RPM
- Comes with a #12 accessory hub



MPM30

30 Qt. Planetary Stand Mixer

Special Features:

- Powerful 3-speed motor; gear-driven transmission to withstand daily use
- Durable 30 qt stainless steel bowl; wire bowl guard for added safety
- Includes wire whip, flat beater, and dough hook
- Easy to use with simple on/off buttons and manually operated bowl lift
- 120V, 1500W, 2 hp, up to 282 RPM
- Comes with a #12 accessory hub



Food Warmer

Lightweight, portable heat with even temperature distribution and simple cleanup.

Specification	MFW1
Capacity	6.3 Gal (24L)
Electrical	120V / 60HZ / 1PH
Power Usage	1200 W
Shipping Weight	13 lbs (5.9 kg)
Net Weight	10 lbs (4.5 kg)
Packaging Dimensions (W x D x H)	13 3/8" x 23" x 9 3/8" (340 x 584 x 238 mm)



MFW1 Food Warmer

Special Features:

- Electric, light-weight food warmer
- Constructed of corrosion resistant stainless steel
- Adjustable thermostat
- Accommodates all standard size serving pans
- Portable and fits most countertop serving areas





Meat Slicers

High-torque precision slicers delivering consistent cuts with safety and ease.

Specification	MS10	MS12
Dimensions (W x D x H)	17 7/10" x 16 3/10" x 13 9/10" (500 x 414 x 355mm)	22" x 20" x 18" (554 x 460 x 423mm)
Cut Capacity / Thickness	8" x 6 1/2" / 9/16" (203 x 165mm) / (143 mm)	9" x 7" / 9/16" (229 x 178mm) / (143 mm)
Blade Diameter	10" (254 mm)	12" (305 mm)
Electrical	120V / 50Hz / 1PH	120V / 50Hz / 1PH
Power Usage	0.2HP	0.33HP
Net Weight	44 lbs (20 kg)	55 lbs (25 kg)



MS10
10" Blade Meat Slicer

Special Features:

- Constructed of stain resistant cast anodized aluminum
- 10" blade diameter
- "High torque" drive system
- 4 rubberized legs prevent slipping or scratching surfaces



MS12
12" Blade Meat Slicer

Special Features:

- Constructed of stain resistant cast anodized aluminum
- 12" blade diameter
- "High torque" drive system
- 4 rubberized legs prevent slipping or scratching surfaces



Beverage Dispensers



Durable, efficient cooling for consistently fresh, chilled beverages.

Specification	MRBD1 (Single Bowl)	MRBD2 (Two Bowls)	MRBD3 (Three Bowls)
Capacity per Bowl	3 gal	3 gal	3 gal
Dimensions (W x D x H)	8" x 17" x 24"	16" x 17" x 24"	24" x 17" x 24"
Gross Weight	42 lbs.	69 lbs.	86 lbs.
Power Usage	120V / 60 Hz / 1PH	120V / 60 Hz / 1PH	120V / 60 Hz / 1PH
Watts	300	420	500



MRBD1
1-Bowl Drink Dispenser



MRBD2
2-Bowl Drink Dispenser



MRBD3
3-Bowl Drink Dispenser

SPECIAL FEATURES:

- Continuous rotary system ensures uniform product consistency
- Durable clear polycarbonate bowls (3-gallon each)
- Stainless steel cooling cylinder, frame, and front panel
- No-drip stainless steel dispensing spout
- Easy push-button operation for efficient service
- Removable drip trays simplify cleaning
- Compact design maximizes counter space
- Engineered for long life with minimal maintenance



mercatorfs.com



Granita Machines

Reliable freezing performance for smooth, evenly blended drinks.

Specification	MFDM2 (2-Bowl)	MFDM3 (3-Bowl)
Capacity per Bowl	12 L (3.2 gal)	18 L (4.8 gal)
Dimensions (W x D x H)	16" x 21" x 27"	24" x 21" x 27"
Weight	66 lbs (30 kg)	88 lbs (40 kg)
Amps	5.5 A	6.2 A
Voltage	120 V / 650 W / 1PH	120 V / 720 W / 1PH
Construction / Housing	Stainless-Steel + ABS Body	Stainless-Steel + ABS Body



MFDM2
2-Bowl Granita Machine



MFDM3
3-Bowl Granita Machine

SPECIAL FEATURES:

- Lighted top panel for vibrant product visibility
- Clear, durable polycarbonate bowls
- Stainless steel cooling cylinder, frame, and front panel
- Continuous agitator for smooth, fresh blends
- Powerful 1/3 HP motor for consistent freezing performance
- Removable drip trays simplify cleaning
- Compact design maximizes counter space
- Engineered for long life with minimal maintenance



mercatorfs.com



Engineered for Performance. Priced for Growth.

MERCATOR

From **cooking equipment and refrigeration to cleanup, food prep, and concession solutions**, Mercator provides a **one-stop source** for durable, ETL-listed food service equipment at highly competitive prices. Backed by fast delivery, strong warranties, and responsive support, Mercator is committed to giving Operations Managers the confidence to focus less on equipment—and more on delivering exceptional dining experiences.

mercatorfs.com

Contact Support

info@mercatorfs.com | 954.292.7171

© 2025 MERCATOR

A proud subsidiary of  - Built on a Legacy of Quality Since 1987.